


# ROOF PATCH and REPAIR

**EFFECTIVE ON:  
Asphalt, Composition, Tile,  
Slate, Felt, Wood & Metal  
Roofing Materials**



**QUICKLY SEALS LEAKS ON:**  
Flat Roofs • Chimney and Sky Light Flashings  
Overlapped Seams • Gutters and Downspouts  
Drip Edges • Mobile Home and Camper Roofs  
Vent Pipe Flashings • Asphalt Shingle Roofs  
Gravel Stops • One Ply Rubberized Systems  
Metal Buildings • Below Grade Foundations  
Off Ridge Vents • Fiberglass Shingle Roofs  
Seams with Pinholes

**NET WT. 14 OZ. (396 Grams)**

**DANGER:**  
**EXTREMELY FLAMMABLE.**  
**CONTENTS UNDER PRESSURE .**  
**SEE OTHER CAUTIONS ON BACK PANEL.**

**Contains NO Chlorinated Solvents**

**NO 1,1,1-Trichloroethane**

**NO Hexane • NO CFC's**

**ROOF PATCH and REPAIR** is a portable, easy to use, thick black aerosol mastic coating that seals water leaks and fills cracks and voids on most roofing surfaces. **ROOF PATCH and REPAIR** is an extremely durable sealer and coating that will not sag or drip in summer heat or crack or peel in winter cold. **ROOF PATCH and REPAIR** sprays as a liquid, flows into low spots, cracks and crevices then dries to a thick, black rubberized coating. Great for asphalt and fiberglass shingles, built-up tar and gravel, 1 ply rubberized and granulated roofs, mobile home and RV roofs, flashings around chimneys, vents and skylights. Helps seal concrete foundations and basements from water seepage and hydrostatic pressure. Provides an effective repair even when the surface is wet. Easy to carry, easy to apply. Eliminates mess, clean-up and burdensome pails.

**Read all instructions before using this product**

**DIRECTIONS: SHAKE WELL.** Shake vigorously until agitator ball inside can rattles freely for one minute. Shake can occasionally throughout application. Spray surface using a sweeping motion from a distance of 12 to 14 inches. For maximum effectiveness, apply several thin coats rather than one thick layer. For best results, use only at can-temperatures above 60°F. Spray a larger area than where leak has occurred and feather edges into surrounding area with lighter applications.

**NOTE:** After each use, invert can and apply a short burst to clear actuator.

**COVERAGE:** One can treats 2 to 12 square feet depending on coating thickness.

**DANGER:** Contains Aliphatic Petroleum Solvent (64742-89-8); Toluene (108-88-3) and Liquefied Petroleum Gas (68476-85-7). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

**KEEP OUT OF REACH OF CHILDREN**

**WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**FIRST AID:**


**EXCESSIVE INHALATION:** Remove victim to fresh air, and call a physician.

**IF SWALLOWED:** Do not induce vomiting, get medical attention immediately.

**IF EYE CONTACT:** Flush with water for 15 minutes, lifting upper and lower lids. Get medical attention.

**IF SKIN CONTACT:** Wash affected area with soap and water. If irritation persists, get medical attention.

**HMIS RATING:** Health, 2; Flammability, 3; Reactivity, 0; Personal Protection, C.



**TERAND INDUSTRIES, INC.**  
FT. LAUDERDALE, FL 33310