

BEFORE YOU START, READ THE APPLICATION INSTRUCTIONS COMPLETELY. MAKE SURE SURFACE HAS BEEN PROPERLY PREPARED. MAKE SURE TEMPERATURE OF FLOOR AND MATERIAL IS BETWEEN 60 & 85 DEGREES FAHRENHEIT. THE FLOOR MUST BE DRY AND FREE OF ALL OILS, GREASE, WAX, AND DIRT. AN ACID ETCH OR PRESSURE WASHING IS RECOMMENDED.

DIRECTION

1. CLEAN & PREPARE ALL AREAS TO BE TREATED.
2. LET AREA DRY COMPLETELY.
3. MIX ONE SET A&B IN BUCKET AT A TIME. SEE A&B CANS IN KIT FOR MIXING INSTRUCTIONS.
4. APPLY TO SURFACE WITH BRUSH, ROLLER, OR TROWEL.
5. WHILE SURFACE IS WET, SPRINKLE NON-SKID GRIT OVER ENTIRE AREA TO BE SKID PROOFED
6. CURING TIME MINIMUM 12 HOURS. 24 HOURS FOR HEAVY TRAFFIC AND 48 HOURS FOR CHEMICAL SPILLAGE

REORDER FROM:

INTERSTATE PRODUCTS, INC.
1-800-IPI-SAY HI
(1-800-474-7294)
FAX 1-800-44-TO FAX
<http://www.interstateproducts.com>



"Quality Environmental Solutions"

TRACTION-N-MORE

For a Slip Proof Easy to Clean Surface

EPOXY NON SKID COATING

**FOR USE ON RAMPS,
VEHICLES, MACHINERY,
DECKS,
AND ANY WHERE A NON SKID
& CHEMICAL RESISTANT
SURFACE IS DESIRED.**

CAUTION:

KEEP OUT OF REACH OF CHILDREN
(SEE SIDE PANELS FOR ADDITIONAL CAUTIONS)
CONTAINS
EPOXY RESIN MIXTURE CAS #97-86-9, 8032-92-4
EPOXY HARDENER CAS # 68910-93-0
SAND CAS#14808-60-7

CAUTION:

AVOID SKIN CONTACT WITH PART A AND B AND THEIR MIXTURE. THE USE OF PROTECTIVE HAND CREAMS OR RUBBER GLOVES IS RECOMMENDED. THOROUGHLY WASH HANDS WITH SOAP AND WATER AFTER USE. AND ESPECIALLY BEFORE EATING OR SMOKING. PROLONGED OR REPEATED EXPOSURE TO THE COMPONENTS MAY CAUSE DERMATITIS OR ALLERGIC REACTIONS IN SOME INDIVIDUAL.

RECOMMENDATIONS & LIMITATIONS:

THIS EPOXY TRACTION-N-MORE HAS BEEN DESIGNED FOR USE ON AREAS WHICH ARE SUBJECTED TO HEAVY ABRASIVE TRAFFIC, IMPACT AND CORROSIVE CHEMICAL SPILLAGE, SUCH AS ACIDS, ALKALIS, BLOOD, FATS, GREASES, OIL, AND MANY OTHER CHEMICALS. DO NOT USE TRACTION-N-MORE ON ASPHALTIC MATERIALS OR WHERE A PERMANENT BOND IS NOT DESIRED. TRACTION-N-MORE MAY BE INSTALLED ON ANY STRUCTURALLY SOUND AND PROPERLY PREPARED CONCRETE, METAL, WOOD, OR CERAMIC TILE SURFACE.

**DO NOT BREATHE VAPORS
MIX IN WELL VENTILATED AREA**